



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot.

1. PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifiers

Product name: **Alcohol Sanitizer**

Mixture of CAS #: 64-17-5, 67-63-0, 58-81-5, 7722-84-1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Sanitizer, Disinfectant

1.3 Details of the supplier of the safety data sheet

Company: Deicing Depot
1580 NW 3rd Street, Deerfield Beach, FL 33442

Telephone : 954- 781-9200

1.4 Emergency telephone number Chemtrec 1- 800-424-9300

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H226

Eye irritation (Category 2A), H319

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H226

Flammable liquid and vapor.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

Precautionary Statements:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.

Response:

- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

Storage:

- P403+233 Store in a well ventilated place. Keep container tightly closed.

Disposal:

- P501 Dispose of contents / container in accordance with local / national regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1

Mixture

Component	CAS#	Concentration
Ethanol	64-17-5	80%
2-Propanol	67-63-0	5-10%
Sterilized Water	7732-18-5	20-28%
Glycerine	56-81-5	1-2%
Hydrogen Peroxide	7722-84-1	<1%

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Move out of dangerous area, consult a physician. Show this safety data sheet to the doctor in attendance.



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labeling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with eyes. Avoid inhalation of vapor or mist.
Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge.
For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Handle and store under inert gas. Hygroscopic

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures

Ensure adequate ventilation, especially in confined areas.



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

Personal Protective Equipment

- Eyes** Wear as appropriate: Goggles, Face-shield
- Inhalation** Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

Exposure Guidelines

- Ethanol** ACGIH STEL 1,000 ppm
OSHA PEL 1,000 ppm 1,900 mg/m³
- 2-Propanol** OSHA PEL 400 ppm 980 mg/m³
ACGIH TLV (8-hour) 200 ppm
ACGIH STEL 400 ppm

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- | | |
|--|----------------------------------|
| a) Appearance | Form: liquid
Color: colorless |
| b) Odor | alcohol-like |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Not measured |
| f) Initial boiling point and boiling range | Not measured |
| g) Flash point | 74 °F - 80 °F closed cup |
| h) Evaporation rate | 3.0 |
| i) Flammability (solid, gas) | No data available |



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

- | | | |
|----|------------------------------|--|
| j) | Upper/lower flammability EL. | Upper/Lower explosion limit:
Not Measured |
| k) | Relative density | 0.86 – 0.90 |

10. STABILITY AND REACTIVITY

10.1 Reactivity

No data available

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Heat, flames and sparks. Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Oxidizing agents, Acid anhydrides, Aluminum, Halogenated compounds, Acids

10.6 Hazardous decomposition products

Other decomposition products - No data available In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Acute toxicity

LD50 Oral - Rat - 5,045 mg/kg

Remarks: Behavioral: Altered sleep time (including change in righting reflex). Behavioral: Somnolence (general depressed activity).

LC50 Inhalation - Rat - 8 h - 16000 ppm



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation - 24 h

Respiratory sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Propanol)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Specific target organ toxicity - single exposure

Inhalation, Oral - May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Additional Information

RTECS: NT8050000

Central nervous system depression, prolonged or repeated exposure can cause: Nausea, Headache, Vomiting, narcosis, Drowsiness, Overexposure may cause mild, reversible liver effects., Aspiration may lead to: Lung edema, Pneumonia

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Kidney - Irregularities - Based on Human Evidence

Kidney - Irregularities - Based on Human Evidence



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish	LC50 - Pimephales promelas (fathead minnow) - 9,640.00 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 5,102.00 mg/l - 24 h
	Immobilization EC50 - Daphnia magna (Water flea) - 6,851 mg/l - 24 h
Toxicity to algae	EC50 - Desmodesmus subspicatus (green algae) - > 2,000.00 mg/l - 72 h
	EC50 - Algae - > 1,000.00 mg/l - 24 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No bioaccumulation is to be expected (log Pow <= 4).

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.



Manufactured for Deicing Depot

SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1170 Class: 3 Packing group: III
Proper shipping name: Ethanol Solutions
Reportable Quantity (RQ):

Poison Inhalation Hazard: No

IMDG

UN number: 1170 Class: 3 Packing group: III EMS-No: F-E, S-D
Proper shipping name: Ethanol Solutions

IATA

UN number: 1170 Class: 3 Packing group: III
Proper shipping name: Ethanol Solutions

Limited Quantity Shipments: Exemption 173.150, PG III, 70% Ethanol or Less, Containers less than 1.3 Gallons, less than 66 lbs per box only need orientation arrows on the box and a limited quantity label, no shipping papers required.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

OSHA Hazards (HCS 1994)

Flammable liquid, Eye irritation

TSCA Inventory Listing

Components

Ethanol
2-Propanol

CAS-No.

64-17-5
67-63-0

SARA 302 Status

Components

CAS-No.

Weight percent

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 311/312 Classification

"Fire hazard", "Immediate (acute) health hazard"

SARA 313 Chemical

Components

2-Propanol

CAS-No.

67-63-0

Weight percent

10-15 %



SAFETY DATA SHEET

Version 1.0
Date 04/23/2020

Manufactured for Deicing Depot

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

none

Reportable Quantity

Weight percent

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65

Components CAS-No.

None

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
H226	Flammable liquid and vapor.
H319	Causes serious eye irritation.

HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0

NFPA Rating

Health hazard:	2
Fire Hazard:	3
Reactivity Hazard:	0

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Clean All & Solvents and Petroleum Service, Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.